

WALL THICKNESS	0.226(5.74)	EXCEPT AS SHOWN

NOTE: BREAK ALL CORNERS WITH 0.015" (.38 MM) RADIUS UNLESS OTHERWISE NOTED. STANDARD TOLERANCES TO APPLY UNLESS OTHERWISE SPECIFIED.

WALL ITTION				<del>,,,</del>	EXCELL 1 110	01101111			
DATE	REV	DESCRIPTION					BY		
03/10/23	2	REMOVED ALLOY					NDZAL		
07/16/15	1		ADDED ±.040 TOLERANCE.					PAUL	
EST.AREA	2.6	80		ın. <sup>2</sup>	EST.AREA	1728	3.746	мм. <sup>2</sup>	
EST.WT.	3.2	215		LBS/FT.	EST.WT.	4.78	5	KG/M.	
EST.PER.	23.	.713		IN.	EST.PER.	602.	304	мм.	
OUT PER.	12.	566		IN.	OUT PER.	319.:	2	мм.	
C.C.D.	4.0	00		IN.	C.C.D.	101.6	300	мм.	
FINISH M/F			ALLOY						
CKD BY	FACTOR	7	SCALE	1:1	DWN BY C.P.	DATE	04/08	3/2008	

## Can Art

ALUMINUM EXTRUSION INC.

85 PARKSHORE DRIVE BRAMPTON, ONT L6T 5M1 TEL. NO. (905) 791-1464 FAX NO. (905) 791-9151 WEB: www.canart.com

THIS DRAWING IS NOT NECESSARILY A COPY OF YOUR ORIGINAL. PLEASE APPROVE DIMENSIONS AND TOLERANCES INDICATED. CAN ART ASSUMES NO RESPONSIBILITY EITHER TECHNICAL OR LEGAL FOR HAVING THIS SHAPE MADE. THE CUSTOMER AGREES TO FULLY PROTECT CAN ART ALUMINUM FROM CLAIMS OF OTHERS RESULTING FROM THIS SHAPE.

SIGNED: \_\_\_\_\_ DATE: \_\_\_\_