



WALL THICKNESS	0.125	(3.18)	EXCEPT AS SHOWN
I WALL ITHORNESS	0.120	(00)	ENGLI I NO SHOWN

NOTE: BREAK ALL CORNERS WITH 0.015" (.38 MM) RADIUS UNLESS OTHERWISE NOTED. STANDARD TOLERANCES TO APPLY UNLESS OTHERWISE SPECIFIED

WALL INICKN	IESS	0.12	3 (3.10)	EXCEPT AS	SHOWIN	
DATE	REV	DESCRIPTION				BY
03/10/23	2	REM□VED ALL□Y				JASON
08/05/99	1	REDRAWN				P.M.
EST.AREA	0.	393	IN. ²	EST.AREA	253	мм. ²
EST.WT.	0.	463	LBS/FT.	EST.WT.	0.690	KG/M.
EST.PER.	6.	283	IN.	EST.PER.	159.6	мм.
OUT PER.	3.	.534	IN.	OUT PER.	89.8	мм.
C.C.D.	1.	125	IN.	C.C.D.	29	мм.
FACTOR 14		FINISH	M/F	ALLOY & TEMP.		
CKD BY		SCALE	2:1	DWN BY C.F	P. DATE 03/	/06/97

Can Art

ALUMINUM EXTRUSION INC.

85 PARKSHORE DRIVE BRAMPTON, ONT L6T 5M1 TEL. NO. (905) 791-1464 FAX NO. (905) 791-9151 E-MAIL: canart@canart.com

THIS DRAWING IS NOT NECESSARILY A COPY OF YOUR ORIGINAL. PLEASE APPROVE DIMENSIONS AND TOLERANCES INDICATED. CAN ART ASSUMES NO RESPONSIBILITY EITHER TECHNICAL OR LEGAL FOR HAVING THIS SHAPE MADE. THE CUSTOMER AGREES TO FULLY PROTECT CAN ART ALUMINUM FROM CLAIMS OF OTHERS RESULTING FROM THIS SHAPE.

SIGNED: ______ DATE: _____