



WALL THICKNESS	0.062 (	1.58)	EXCEPT AS SHOWN
WALL IIIICKINLSS	0.002 (	1.00,	LACEFT AS SHOWIN

NOTE: BREAK ALL CORNERS WITH 0.015" (.38 MM) RADIUS UNLESS OTHERWISE NOTED. STANDARD TOLERANCES TO APPLY UNLESS OTHERWISE SPECIFIED.

WALL ITICKINESS C.COZ (1.00) EXCEPT AS SHOWN								
DATE	REV		BY					
03/10/23	4		JASON					
01/24/07	3		PAUL					
EST.AREA	0.2	280		IN. <sup>2</sup>	EST.AREA	180.705	мм. <sup>2</sup>	
EST.WT.	0.5	331		LBS/FT.	EST.WT.	0.492	KG/M.	
EST.PER.	9.0	35		IN.	EST.PER.	229.495	мм.	
OUT PER.	4.7	<sup>7</sup> 12		IN.	OUT PER.	119.7	мм.	
C.C.D.	1.5	00		IN.	C.C.D.	38.100	мм.	
FINISH M/F			ALLOY					
CKD BY	FACTOR	27	SCALE	2:1	DWN BY ${f J.D.}$	DATE 04/11	/1992	

## Can Art

ALUMINUM EXTRUSION INC.

85 PARKSHORE DRIVE BRAMPTON, ONT L6T 5M1 TEL. NO. (905) 791-1464 FAX NO. (905) 791-9151 WEB: www.canart.com

THIS DRAWING IS NOT NECESSARILY A COPY OF YOUR ORIGINAL. PLEASE APPROVE DIMENSIONS AND TOLERANCES INDICATED. CAN ART ASSUMES NO RESPONSIBILITY EITHER TECHNICAL OR LEGAL FOR HAVING THIS SHAPE MADE. THE CUSTOMER AGREES TO FULLY PROTECT CAN ART ALUMINUM FROM CLAIMS OF OTHERS RESULTING FROM THIS SHAPE.

SIGNED: \_\_\_\_\_ DATE: \_\_\_\_