

WALL THICKNESS 0.125 (3.18) EXCEPT AS SHOWN

NOTE: BREAK ALL CORNERS WITH 0.015" (.38 MM) RADIUS UNLESS OTHERWISE NOTED. STANDARD TOLERANCES TO APPLY UNLESS OTHERWISE SPECIFIED

DATE	REV	REV			DESCRIPTION			
03/10/23	1	F			EMOVED ALLOY		JASON	
EST.AREA	1.9	14		IN. ²	EST.AREA	1235.109	мм. ²	
EST.WT.	2.2	297		LBS/FT.	EST.WT.	3.419	KG/M.	
EST.PER.	30	.631		IN.	EST.PER.	778.015	мм.	
OUT PER.	15.	708		IN.	OUT PER.	399.0	MM.	
C.C.D.	5.0	000		IN.	C.C.D.	127.000	MM.	
FINISH M/F					ALLOY			
CKD BY	FACTOR	13	SCALE	1:1	DWN BY $J.T.$	DATE 03/20/2	009	

Can Art

ALUMINUM EXTRUSION INC.

428 JUTRAS DRIVE S. WINDSOR, ON N8N 5C5 TEL. NO. (519) 727-4399 FAX NO. (519) 727-6434 WEB: www.canart.com

THIS DRAWING IS NOT NECESSARILY A COPY OF YOUR ORIGINAL. PLEASE APPROVE DIMENSIONS AND TOLERANCES INDICATED. CAN ART ASSUMES NO RESPONSIBILITY EITHER TECHNICAL OR LEGAL FOR HAVING THIS SHAPE MADE. THE CUSTOMER AGREES TO FULLY PROTECT CAN ART ALUMINUM FROM CLAIMS OF OTHERS RESULTING FROM THIS SHAPE.

SIGNED: _	DAT	E: