
R PROPOSAL No. S-10653
 -



WALL THICKNESS (AS SHOWN) EXCEPT AS SHOWN

NOTE: BREAK ALL CORNERS WITH 0.015" (.38 MM) RADIUS UNLESS OTHERWISE NOTED. STANDARD TOLERANCES TO APPLY UNLESS OTHERWISE SPECIFIED.

DATE	REV	DESCRIPTION				
03/17/23	1	REMO√ED ALLOY				
EST.AREA	0.3	75	IN. ²	EST.AREA	241.937	мм. ²
EST.WT.	0.442		LBS/FT.	EST.WT.	0.659	KG/M.
EST.PER.	3.5	00	IN.	EST.PER.	88.900	мм.
OUT PER.			IN.	OUT PER.		мм.
C.C.D.	1.5	21	IN.	C.C.D.	38.626	мм.
FACTOR 8		FINISH	M/F	ALLOY & TEMP.		
CKD BY		SCALE	1:1	DWN BY C.F	P. DATE 01/15/	/2001

Can Art

ALUMINUM EXTRUSION INC.

85 PARKSHORE DRIVE BRAMPTON, ONT LGT 5M1 TEL. NO. (905) 791—1464 FAX NO. (905) 791—9151 E—MAIL: canart@canart.com

THIS DRAWING IS NOT NECESSARILY A COPY OF YOUR ORIGINAL. PLEASE APPROVE DIMENSIONS AND TOLERANCES INDICATED. CAN ART ASSUMES NO RESPONSIBILITY EITHER TECHNICAL OR LEGAL FOR HAVING THIS SHAPE MADE. THE CUSTOMER AGREES TO FULLY PROTECT CAN ART ALUMINUM FROM CLAIMS OF OTHERS RESULTING FROM THIS SHAPE.